

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

1 IDENTIFICATION OF THE ARTICLE AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier

Trade name: K-FLEX K-400

UFI: T691-T0SP-C00R-74V2

1.2 Relevant identified uses of the article/mixture and uses advised against

Solvent-based adhesive, sealant for industrial and professional uses

1.3 Details of the supplier of the information sheet

Manufacturer/Supplier:

L'ISOLANTE K-FLEX S.p.A.

via Don Locatelli, 35 20877 Roncello (MB) ITALY

Tel. +39 039 6824.1

e-mail: Kflex-Reach@kflex.com

Further information obtainable from: R&D Dept.

1.4 Emergency telephone number

Tel. +39 039 6824.1 (9:00 - 17:00) ITALIA Centro Antiveleni Ospedale Niguarda "Ca' Granda" MILANO tel. 02/66101029; Fondazione Maugeri - Clinica del lavoro e della Riabilitazione PAVIA tel. 0382/24444; Centro Documentazione Tossicologica - Università degli Studi PADOVA tel. 049/8275078; Centro Antiveleni Istituto Scientifico "G. Gaslini" GENOVA tel. 010/5636245; Centro Antiveleni Azienda Ospedaliera "Careggi" FIRENZE tel. 055/4277328; Centro Antiveleni "Policlinico Gemelli" ROMA tel. 06/3054343; Centro Antiveleni Università degli Studi di Roma "La Sapienza" ROMA tel. 06/49970698; Centro Antiveleni Azienda Ospedaliera "A. Cardarelli" NAPOLI tel. 081/7472870; Centro antiveleni Azienda Ospedaliera Universitaria FOGGIA tel. 0881/731111 AUSTRIA Vergiftungsinformationszentrale +43 1 406 43 43 BELGIUM Centre Antipoisons-Antigifocentrum +32 30245245 BULGARIA National Toxicology Centre at National Clinical Toxicology Centre +359 2 9154 233 CROATIA Poison Control Centre Zagreb +385 1 2348342 CZECH REPUBLIC Toxicological Information Centre + 420224919 293 DENMARK Poison Information Centre n +45 82 12 12 12 ESTONIA Estonian Poison Information centre +372 626 93 90 FRANCE Centre Antipoison et de Toxicovigilance de Angers +33 2 41 35 33 30 HUNGARY Health Toxicology Information Service +36 80 20 11 99 IRELAND Poison Information Centre of Ireland +353 1 809 2166 LATVIA Valsts Toksikologijas centrs + 371 67042473 LITHUANIA Lithuania Poison Control and Information Bureau +370 5 236 20 52 NORGE Giftinformasjonen : 22 59 13 00 (døgnåpen) PORTUGAL CIAV Centro de Informacao Antivelenos +351 808 250 143 SLOVAKIA National Toxicological Information Center +421 2 54 774 166 POLAND Informacja toksykologiczna w Polsce +48 42 631 47 24 (czynna 7:00-15:00) SPAIN Instituto Nacional de Toxicologia +34 156 20420

2 HAZARDS IDENTIFICATION

2.1 Classification of the article/mixture

K-FLEX K-400 ADHESIVE

Page n. 1 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/830.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2 H225 Highly flammable liquid and vapour.

Eye irritation, category 2 H319 Causes serious eye irritation.

Skin sensitization, category 1 B H317 May cause an allergic skin reaction.

Specific target organ toxicity - single exposure, category 3 H336 May cause drowsiness or dizziness.

Hazardous to the aquatic environment, chronic toxicity, category 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



Signal word Danger

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/ protective clothing / eye protection / face protection.

P370+P378 In case of fire: use CO2 to extinguish.

P273 Avoid release to the environment.

P391 Collect spillage.

P261 Avoid breathing dust / fume / gas / mist / vapours / spray.

Contains: Formaldehyde, polymer with 4- (1,1-dimethyl) phenol and phenol

Formaldehyde, polymer with 1,3-benzenediol and 4- (1,1-dimethylethyl) phenol

K-FLEX K-400 ADHESIVE

Page n. 2 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

HYDROCARBONS, C6-C7, ISOALCANS, CYCLICS, <5% n-HEXANE

ACETONE

ROSIN

2.3 Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.The product does not contain substances with endocrine disrupting properties in concentration $\geq$ 0.1%.**3 COMPOSITION/INFORMATION ON INGREDIENTS**

3.1 Substances

n.a.

3.2 Article/Mixtures

Contains:		
Identification	x = Conc. %	Classification 1272/2008 (CLP)
HYDROCARBONS, C6-C7, ISOALCANS, CYCLICS, <5% n-HEXANE		
CAS EC 926-605-8 INDEX 649-341-00-2 Reg. no. 01-2119486291-36	32,5 $\leq$ x < 35	Flam. Liq. 2 H225, Asp. Tox. 1 H304, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066, Classification note/notes according to Annex VI to the CLP Regulation: P
ACETONE		
CAS 67-64-1 EC200-662-2 INDEX 606-001-00-8 Reg. no. 01-2119471330-49	30 $\leq$ x < 32,5	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
ETHYL ACETATE		
CAS 141-78-6 EC 205-500-4 INDEX 607-022-00-5 Reg. no. 01-2119475103-46	8 $\leq$ x < 9	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
Formaldehyde, polymer with 4- (1,1-dimethyl) phenol and phenol		

K-FLEX K-400 ADHESIVE

Page n. 3 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

CAS 28453-20-5 EC INDEX	$5 \leq x < 6$	Skin Sens. 1B H317
HYDROCARBONS C6 ISOALCANS <5% n-HEXANE		
CAS 64742-49-0 EC 931-254-9 INDEX 649-328-00-1 Reg. no. 01-2119484651-34	$5 \leq x < 6$	Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 2 H411, Classification note/notes according to Annex VI to the CLP Regulation: P
Formaldehyde, polymer with 1,3-benzenediol and 4- (1,1-dimethylethyl) phenol		
CAS 59633-97-5 EC INDEX	$1 \leq x < 1,5$	Skin Sens. 1B H317
ROSIN		
CAS 8050-09-7 EC 232-475-7 INDEX 650-015-00-7 Reg. no. 01-2119480418-32	$0,7 \leq x < 0,8$	Skin Sens. 1 H317
METHANOL		
CAS 67-56-1 EC 200-659-6 INDEX 603-001-00-X	$0 \leq x < 0,05$	Flam. Liq. 2 H225, Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT SE 1 H370 STOT SE 2 H371: $\geq 3\%$ STA Oral: 100 mg/kg, STA Dermal: 300 mg/kg, STA Inhalation mists/powders: 0,501 mg/l, STA Inhalation vapours: 3 mg/l
FORMALDEHYDE		
CAS 50-00-0 EC 200-001-8 INDEX 605-001-00-5 Reg. no. 01-2119488953-20	$0 \leq x < 0,05$	Carc. 1B H350, Muta. 2 H341, Acute Tox. 2 H330, Acute Tox. 3 H301, Acute Tox. 3 H311, Skin Corr. 1B H314, Eye Dam. 1 H318, STOT SE 3 H335, Skin Sens. 1 H317, Classification note according to Annex VI to the CLP Regulation: B, D Skin Corr. 1B H314: $\geq 25\%$, Skin Irrit. 2 H315: $\geq 5\%$, Skin Sens. 1 H317: $\geq 0,2\%$, Eye Dam. 1 H318: $\geq 25\%$, Eye Irrit. 2 H319: $\geq 5\%$, STOT SE 3 H335: $\geq 5\%$ LD50 Oral: 100 mg/kg, LD50 Dermal: 270 mg/kg, STA Inhalation vapours: 0,501 mg/l

The full wording of hazard (H) phrases is given in section 16 of the sheet.

4 FIRST AID MEASURES

4.1 Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

K-FLEX K-400 ADHESIVE

Page n. 4 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2 Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3 Indication of any immediate medical attention and special treatment needed

Information not available

5 FIRE-FIGHTING MEASURES

5.1 Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2 Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3 Advice for fire-fighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6 ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both

K-FLEX K-400 ADHESIVE

Page n. 5 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2 Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3 Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4 Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7 HANDLING AND STORAGE

7.1 Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges.

When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2 Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight.

Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany): 3

7.3 Specific end use(s)

See the exposure scenarios attached to this safety datasheet.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

K-FLEX K-400 ADHESIVE

Page n. 6 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

BGR България НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)

CZE Česká Republika Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů

DEU Deutschland Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56

DNK. Danmark Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019

ESP España Límites de exposición profesional para agentes químicos en España 2021

EST Eesti Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse nõuded ning töökeskkonna keemiliste ohutegurite piirnõrmi [RT I, 17.10.2019, 1 - jõust. 17.01.2020]

FRA France Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS

FIN Suomi. HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH

HÄLSOVÄRDSMINISTERIETS PUBLIKATIONER 2020:25

GRC Ελλάδα Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία"»

HUN. Magyarország Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelethez a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről

HRV. Hrvatska Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)

ITA Italia. Decreto Legislativo 9 Aprile 2008, n.81

LTU Lietuva Jsakymas dėl lietuvis higienos normos hn 23:2011 „cheminių medžiagų profesinio poveikio ribiniai dydžiai. Matavimo ir poveikio vertinimo bendrieji reikalavimai“ patvirtinimo

LVA Latvija Grozījumi Ministru kabineta 2007. gada 15. maija noteikumos Nr. 325 "Darba aizsardzības prasības saskarē ar ķīmiskajām vielām darba vietās" (prot. Nr. 32 18. §; prot. Nr. 1 22. §)

NOR Norge Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. august 2018 nr. 1255

NLD Nederland Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit

PRT Portugal Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos

POL Polska Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy

K-FLEX K-400 ADHESIVE

Page n. 7 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

ROU România Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006

SWE Sverige Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1)

SVK Slovensko NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénym faktorom pri práci v znení neskorších predpisov

SVN Slovenija Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)

TUR Türkiye Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733

GBR United Kingdom EH40/2005 Workplace exposure limits (Fourth Edition 2020)

EU OEL EU Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.

TLV-ACGIH ACGIH 2021

HYDROCARBONS, C6-C7, ISOALCANS, CYCLICS, <5% n-HEXANE					
Threshold Limit Value					
Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
VLEP	ITA	400	115		

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				1301 mg/kg bw/d				
Inhalation				1131 mg/m3				5306 mg/m3
Skin				1377 mg/kg bw/d				13964 mg/kg bw/d

ROSIN

K-FLEX K-400 ADHESIVE

Page n. 8 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	1				INHAL
GVI/KGVI	HRV	0,05		0,15		
RV	LVA	4				
TLV	ROU	0,1				
WEL	GBR	0,05		0,15		
TLV-ACGIH		0,001				

Predicted no-effect concentration - PNEC

Normal value in fresh water 0,002 mg/l

Normal value in marine water 0 mg/l

Normal value for fresh water sediment 0,007 mg/kg/d

Normal value for marine water sediment 0,001 mg/kg/d

Normal value of STP microorganisms 1000 mg/l

Normal value for the terrestrial compartment 0 mg/kg/d

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation						10 mg/m3		
Skin								2,131 mg/kg bw/d

METHANOL						
Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	260	200			SKIN
TLV	CZE	250	187,75	1000	751	SKIN

K-FLEX K-400 ADHESIVE

Page n. 9 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

AGW	DEU	270	200	1080	800	SKIN
MAK	DEU	130	100	260	200	SKIN
TLV	DNK	260	200			SKIN E
VLA	ESP	266	200			SKIN
TLV	EST	250	200	350	250	SKIN
VLEP	FRA	260	200	1300	1000	SKIN 11
HTP	FIN	270	200	330	250	SKIN
TLV	GRC	260	200	325	250	
AK	HUN	260				SKIN
GVI/KGVI	HRV	260	200			SKIN
VLEP	ITA	260	200			SKIN
RD	LTU	260	200			SKIN
RV	LVA	260	200			SKIN
TLV	NOR	130	100			SKIN
TGG	NLD	133				SKIN
VLE	PRT	260	200			SKIN
NDS/NDSch	POL	100		300		SKIN
TLV	ROU	260	200			SKIN
NGV/KGV	SWE	250	200	350 (C)	250 (C)	SKIN
NPEL	SVK	260	200			SKIN
MV	SVN	260	200	1040	800	SKIN
ESD	TUR	260	200			SKIN
WEL	GBR	266	200	333	250	SKIN
OEL	EU	260	200			
TLV-ACGIH		262	200	328	250	SKIN

FORMALDEHYDE						
Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	

K-FLEX K-400 ADHESIVE

Page n. 10 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

TLV	BGR	1		2		
TLV	CZE	0,5	0,4005	1	0,801	
AGW	DEU	0,37	0,3	0,74	0,6	
TLV	DNK			0,4 (C)	0,3 (C)	
VLA	ESP	0,37	0,3	0,74	0,6	
TLV	EST	0,6	0,5	1,2 (C)	1 (C)	
VLEP	FRA	0,37	0,3	0,74	0,6	
HTP	FIN	0,37	0,3	0,74	0,6	
TLV	GRC	0,37	0,3	0,74	0,6	
AK	HUN	0,6		0,6		SKIN
GVI/KGVI	HRV	0,37	0,3	0,74	0,6	
VLEP	ITA	0,37	0,3	0,74	0,6	
RD	LTU	0,37	0,3	0,74	0,6	
RV	LVA	0,5				
TLV	NOR	0,6	0,5	1,2 (C)	1 (C)	
TGG	NLD	0,15		0,5		
VLE	PRT	0,37	0,3	0,74	0,6	
NDS/NDSch	POL	0,37		0,74		SKIN
TLV	ROU	0,37	0,3	0,74	0,6	
NGV/KGV	SWE	0,37	0,3	0,74	0,6	SKIN
NPEL	SVK	0,37	0,3	0,74	0,6	
MV	SVN	0,62	0,5	0,62	0,5	SKIN
WEL	GBR	2,5	2	2,5	2	
OEL	EU	0,37	0,3	0,74	0,6	
TLV-ACGIH			0,1		0,3	

Predicted no-effect concentration - PNEC

Normal value in fresh water 0,44 mg/l

Normal value in marine water 0,44 mg/l

Normal value for fresh water sediment 2,3 mg/kg/d

Normal value for marine water sediment 2,3 mg/kg/d

K-FLEX K-400 ADHESIVE

Page n. 11 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

Normal value of STP microorganisms 0,19 mg/l

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				4,1 mg/kg bw/d				
Inhalation			0,1 mg/m3	3,2 mg/m3	1 mg/m3		0,375 mg/m3	9 mg/m3
Skin			0,012 mg/cm2	102 mg/kg bw/d			0,037 mg/cm2	240 mg/kg bw/d

ACETONE						
Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	600		1400		
TLV	CZE	800	331,2	1500	621	
AGW	DEU	1200	500	2400 (C)	1000 (C)	
MAK	DEU	1200	500	2400	1000	
TLV	DNK	600	250			E
VLA	ESP	1210	500			
TLV	EST	1210	500			
VLEP	FRA	1210	500	2420	1000	
HTP	FIN	1200	500	1500	630	
TLV	GRC	1780		3560		
AK	HUN	1210				
GVI/KGVI	HRV	1210	500			
VLEP	ITA	1210	500			
RD	LTU	1210	500	2420	1000	
RV	LVA	1210	500			SKIN

K-FLEX K-400 ADHESIVE

Page n. 12 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

TLV	NOR	295	125			
TGG	NLD	1210		2420		
VLE	PRT	1210	500			
NDS/NDSch	POL	600		1800		
TLV	ROU	1210	500			
NGV/KGV	SWE	600	250	1200 (C)	500 (C)	
NPEL	SVK	1210	500			
MV	SVN	1210	500	2420	1000	
ESD	TUR	1210	500			
WEL	GBR	1210	500	3620	1500	
OEL	EU	1210	500			
TLV-ACGIH			250		500	

Predicted no-effect concentration - PNEC

Normal value in fresh water 10,6 mg/l

Normal value in marine water 1,06 mg/l

Normal value for fresh water sediment 30,4 mg/kg/d

Normal value for marine water sediment 3,04 mg/kg/d

Normal value of STP microorganisms 100 mg/l

Normal value for the terrestrial compartment 29,5 mg/kg/d

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				62 mg/kg bw/d				
Inhalation				200 mg/m3	2420 mg/m3			1210 mg/m3
Skin				62 mg/kg bw/d				186 mg/kg bw/d

ETHYL ACETATE

K-FLEX K-400 ADHESIVE

Page n. 13 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	734	200	1468	400	
TLV	CZE	700	191,1	900	245,7	
AGW	DEU	730	200	1460	400	
MAK	DEU	750	200	1500	400	
TLV	DNK	540	150			E
VLA	ESP	734	200	1468	400	
TLV	EST	500	150	1100	300	
VLEP	FRA	734	200	1468	400	
HTP	FIN	730	200	1470	400	
TLV	GRC	734	200	1468	400	
AK	HUN	734		1468		
GVI/KGVI	HRV	734	200	1468	400	
VLEP	ITA	734	200	1468	400	
RD	LTU	500	150	1100 C)	300 (C)	
RV	LVA	200	54	1468	400	
TLV	NOR	734	200			
TGG	NLD	734		1468		
VLE	PRT	734	200	1468	400	
NDS/NDSch	POL	734		1468		
TLV	ROU	734	200	1468	400	
NGV/KGV	SWE	550	150	1100	300	
NPEL	SVK	734	200	1468	400	
MV	SVN	734	200	1468	400	
WEL	GBR	734	200	1468	400	
OEL	EU	734	200	1468	400	
TLV-ACGIH		1441	400			

Predicted no-effect concentration - PNEC

K-FLEX K-400 ADHESIVE

Page n. 14 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

Normal value in fresh water 0,24 mg/l

Normal value in marine water 0,024 mg/l

Normal value for fresh water sediment 1,15 mg/kg/d

Normal value for marine water sediment 0,115 mg/kg/d

Normal value of STP microorganisms 650 mg/l

Normal value for the food chain (secondary poisoning) 0,2 g/kg/food

Normal value for the terrestrial compartment 0,148 mg/kg/d

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				4,5 mg/kg bw/d				
Inhalation	734 mg/m3	734 mg/m3	367 mg/m3	367 mg/m3	1468 mg/m3	1468 mg/m3	734 mg/m3	734 mg/m3
Skin				37 mg/kg bw/d				63 mg/kg bw/d

HYDROCARBONS C6 ISOALCANS <5% n-HEXANE								
Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				1301 mg/kg bw/d				
Inhalation				1131 mg/m3				5306 mg/m3
Skin				1377 mg/kg bw/d				13964 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ;

LOW = low hazard; MED = medium hazard ; HIGH = high hazard.

8.2 Exposure controls

K-FLEX K-400 ADHESIVE

Page n. 15 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

When choosing risk management measures and operating conditions, consult the exposure scenarios attached.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type

AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

K-FLEX K-400 ADHESIVE

Page n. 16 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

For information on controlling environmental exposure, see the exposure scenarios attached to this safety datasheet.

9 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Properties	Value	Informazioni
Appearance	liquid	
Colour	dark brown	
Odour	characteristic of solvent	
Melting point / freezing point	-94,7 °C	Substance:ACETONE
Initial boiling point	56,5 °C	Substance:ACETONE
Flammability	flammable liquid	
Lower explosive limit	1,2 % (v/v)	Substance:HYDROCARBONS, C6-C7, ISOALCANS, CYCLICS, <5% n-HEXANE
Upper explosive limit	13 % (v/v)	Substance:ACETONE
Flash point	-19 °C	Substance:HYDROCARBONS, C6-C7, ISOALCANS, CYCLICS, <5% n-HEXANE
Auto-ignition temperature	> 200 °C	
Decomposition temperature	not available	
pH	not available	Reason for missing data:substance/mixture is non-soluble (in water)
Kinematic viscosity	>20,5 mm ² /sec (40°C)	
Dynamic viscosity	680 mPa.s	Temperature: 20 °C
Solubility	insoluble in water	
Partition coefficient: n-octanol/water	not available	Reason for missing data:The product is a mixture
Vapour pressure	240 hPa	Substance:ACETONE Temperature: 20 °C
Density and/or relative density	0,85 g/cm ³	Temperature: 20 °C

K-FLEX K-400 ADHESIVE

Page n. 17 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

Relative vapour density	2,01	Substance:ACETONE Temperature: 20 °C
Particle characteristics	not applicable	

9.2 Other information

Information with regard to physical hazard classes

Information not available

Other safety characteristics

VOC (Directive 2010/75/EU) 77,84 % - 661,60 g/litre

VOC (volatile carbon) 61,57 % - 523,35 g/litre

Total solids 22,4%

10 STABILITY AND REACTIVITY

10.1 Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

FORMALDEHYDE

Decomposes under the effect of heat.

Aqueous solutions are stabilised with methanol but tend to polymerise over time.

ACETONE

Decomposes under the effect of heat.

ETHYL ACETATE

Decomposes slowly into acetic acid and ethanol under the effect of light, air and water.

10.2 Chemical stability

The product is stable in normal conditions of use and storage.

10.3 Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

FORMALDEHYDE

Risk of explosion on contact with: nitromethane, nitrogen dioxide, hydrogen peroxide, phenoles, performic acid, nitric acid. May polymerise on contact with: strong oxidising agents, alkalis. May react dangerously with: hydrochloric acid, magnesium carbonate, sodium hydroxide, perchloric acid, aniline. Forms explosive mixtures with: air.

ACETONE

Risk of explosion on contact with: bromine trifluoride, fluorine dioxide, hydrogen peroxide, nitrosyl chloride, 2-methyl-1, 3 butadiene, nitromethane, nitrosyl perchlorate. May react dangerously with: potassium tert-butoxide, alkaline hydroxides, bromine, bromoform, isoprene, sodium, sulphur dioxide, chromium trioxide, chromyl chloride, nitric acid, chloroform, peroxy monosulphuric acid, phosphoryl oxychloride, chromosulphuric acid, fluorine, strong oxidising agents,

K-FLEX K-400 ADHESIVE

Page n. 18 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

strong reducing agents. Develops flammable gas on contact with: nitrosyl perchlorate.

ETHYL ACETATE

Risk of explosion on contact with: alkaline metals, hydrides, oleum. May react violently with: fluorine, strong oxidising agents, chlorosulphuric acid, potassium tert-butoxide. Forms explosive mixtures with: air.

10.4 Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

FORMALDEHYDE

Avoid exposure to: light, sources of heat, naked flames.

ACETONE

Avoid exposure to: sources of heat, naked flames.

ETHYL ACETATE

Avoid exposure to: light, sources of heat, naked flames.

10.5 Incompatible materials

FORMALDEHYDE

Incompatible with: acids, alkalis, ammonia, tannin, strong oxidants, phenoles, copper salts, silver, iron.

ACETONE

Incompatible with: acids, oxidising substances.

ETHYL ACETATE

Incompatible with: acids, bases, strong oxidants, aluminium, nitrates, chlorosulphuric acid. Incompatible materials: plastic materials.

10.6 Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

FORMALDEHYDE

When heated to decomposition releases: methanol, carbon monoxide.

ACETONE

May develop: ketenes, irritant substances.

11 TOXICOLOGICAL INFORMATION

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

K-FLEX K-400 ADHESIVE

Page n. 19 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

Information on likely routes of exposure

METHANOL

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

METHANOL

The minimum lethal dose for humans by ingestion is considered to be in the range from 300 to 1000 mg/kg. Ingestion of 4-10 ml of the substance may cause permanent blindness in adult humans (IPCS).

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture: Not classified (no significant component)

ATE (Oral) of the mixture: Not classified (no significant component)

ATE (Dermal) of the mixture: Not classified (no significant component)

HYDROCARBONS, C6-C7, ISOALCANS, CYCLICS, <5% n-HEXANE

LD50 (Dermal): > 2000 mg/kg Rabbit

LD50 (Oral): > 3350 mg/kg Rat

LC50 (Inhalation vapours): > 20 mg/l/4h Rat

ROSIN

LD50 (Dermal): > 2000 mg/kg

LD50 (Oral): 2800 mg/kg Rat

FORMALDEHYDE

LD50 (Dermal): 270 mg/kg Rabbit

LD50 (Oral): 100 mg/kg Rat

LC50 (Inhalation vapours): 0,165 ppm Rat

ACETONE

LD50 (Dermal): 20000 mg/kg Rabbit

LD50 (Oral): 5800 mg/kg Rat

ETHYL ACETATE

K-FLEX K-400 ADHESIVE

Page n. 20 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

LD50 (Dermal): > 20000 mg/kg bw Rabbit

LD50 (Oral): 4934 mg/kg dw Rat - Metodo OCSE 401

LC50 (Inhalation vapours): > 6000 ppm/6h Rat

HYDROCARBONS C6 ISOALCANS <5% n-HEXANE

LD50 (Dermal): 3350 mg/kg Rabbit

LD50 (Oral): 16750 mg/kg Rat

LC50 (Inhalation vapours): 259,3 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: >20,5 mm²/sec (40°C)

11.2 Information on other hazards

K-FLEX K-400 ADHESIVE

Page n. 21 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

12 ECOLOGICAL INFORMATION

12.1 Toxicity

HYDROCARBONS, C6-C7, ISOALCANS, CYCLICS, <5% n-HEXANE

LC50 - for Fish 12 mg/l/96h Oncorhynchus mykiss

EC50 - for Crustacea 3 mg/l/48h Daphnia Magna

EC50 - for Algae / Aquatic Plants 55 mg/l/72h Pseudokirchneriella subcapitata

FORMALDEHYDE

LC50 - for Fish 6,9 mg/l/144h Zebra danio (Danio rerio)

EC50 - for Crustacea 4,3 mg/l/48h Pulce d'acqua (Daphnia pulex)

ETHYL ACETATE

LC50 - for Fish 230 mg/l/96h Pimephales promelas

EC50 - for Crustacea 165 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants > 100 mg/l/72h Scenedesmus subspicatus

Chronic NOEC for Crustacea 2,4 mg/l 21 day - Daphnia pulex

HYDROCARBONS C6 ISOALCANS <5% n-HEXANE

EC50 - for Crustacea 31,9 mg/l/48h

EC50 - for Algae / Aquatic Plants 13,6 mg/l/72h

Chronic NOEC for Fish 4,09 mg/l 28 days

Chronic NOEC for Algae / Aquatic Plants 3 mg/l

12.2 Persistence and degradability

ROSIN

Solubility in water 0,1 - 100 mg/l

Rapidly degradable

METHANOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

FORMALDEHYDE

Solubility in water 55000 mg/l

Rapidly degradable

K-FLEX K-400 ADHESIVE

Page n. 22 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

ACETONE

NOT rapidly degradable

ETHYL ACETATE

Solubility in water > 10000 mg/l

Rapidly degradable

HYDROCARBONS C6 ISOALCANS <5% n-HEXANE

Rapidly degradable

12.3 Bioaccumulative potential

HYDROCARBONS, C6-C7, ISOALCANS, CYCLICS, <5% n-HEXANE

Partition coefficient: n-octanol/water < 4 Log Kow

ROSIN

Partition coefficient: n-octanol/water 3

BCF 56,23

METHANOL

Partition coefficient: n-octanol/water -0,77

BCF 0,2

FORMALDEHYDE

Partition coefficient: n-octanol/water 0,35

BCF < 1

ACETONE

Partition coefficient: n-octanol/water -0,23

BCF 3

ETHYL ACETATE

Partition coefficient: n-octanol/water 0,68

BCF 30

HYDROCARBONS C6 ISOALCANS <5% n-HEXANE

Partition coefficient: n-octanol/water 3,6 Log Kow

BCF < 2500

12.4 Mobility in soil

K-FLEX K-400 ADHESIVE

Page n. 23 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

ROSIN

Partition coefficient: soil/water 3,7289

FORMALDEHYDE

Partition coefficient: soil/water 1,202

HYDROCARBONS C6 ISOALCANS <5% n-HEXANE

Partition coefficient: soil/water 1,78

12.5 Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

12.6 Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7 Other adverse effects

Information not available

13 DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14 TRANSPORT INFORMATION

14.1 UN number or ID number

ADR / RID, IMDG, IATA: 1133

14.2 UN proper shipping name

ADR / RID: ADHESIVES

IMDG: ADHESIVES

IATA: ADHESIVES

14.3 Transport hazard class(es)

K-FLEX K-400 ADHESIVE

Page n. 24 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3

**14.4 Packing Group**

ADR / RID, IMDG, IATA: II

14.5 Environmental hazards

ADR / RID: Environmentally Hazardous



IMDG: Marine Pollutant



IATA: NO

For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

14.6 Special Precautions for User

ADR / RID:	HIN - Kemler: 33 Special provision: 640D	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
IMDG:	EMS: F-E, S-D	Limited Quantities: 5 L	
IATA:	Cargo: Pass.: Special provision:	Maximum quantity: 60 L Maximum quantity: 5 L A3	Packaging instructions: 364 Packaging instructions: 353

14.7 Maritime transport in bulk according to IMO instruments

Information not relevant

15 REGULATORY INFORMATION

K-FLEX K-400 ADHESIVE

Page n. 25 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

15.1 Safety, health and environmental regulations/legislation specific for the article/mixture

Seveso Category - Directive 2012/18/EU: E2-P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Point 72 FORMALDEHYDE

REACH Reg.: 01-2119488953-20

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Regulated explosives precursor

The acquisition, introduction, possession or use of that regulated explosives precursor by members of the general public is subject to reporting obligations as set out in Article 9.

All suspicious transactions and significant disappearances and thefts must be reported to the relevant national contact point.

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage $\geq$ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 3: Severe hazard to waters

K-FLEX K-400 ADHESIVE

Page n. 26 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

15.2 Chemical Safety Assessment

A chemical safety assessment has been performed for the following contained substances

ETHYL ACETATE

16 OTHER INFORMATION

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2 Flammable liquid, category 2

Carc. 1B Carcinogenicity, category 1B

Muta. 2 Germ cell mutagenicity, category 2

Acute Tox. 2 Acute toxicity, category 2

Acute Tox. 3 Acute toxicity, category 3

STOT SE 1 Specific target organ toxicity - single exposure, category 1

Asp. Tox. 1 Aspiration hazard, category 1

Skin Corr. 1B Skin corrosion, category 1B

Eye Irrit. 2 Eye irritation, category 2

Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Skin Sens. 1 Skin sensitization, category 1

Skin Sens. 1B Skin sensitization, category 1B

Aquatic Chronic 2 Hazardous to the aquatic environment, chronic toxicity, category 2

H225 Highly flammable liquid and vapour.

H350 May cause cancer.

H341 Suspected of causing genetic defects.

H330 Fatal if inhaled.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H370 Causes damage to organs.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

K-FLEX K-400 ADHESIVE

Page n. 27 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament

K-FLEX K-400 ADHESIVE

Page n. 28 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

K-FLEX K-400 ADHESIVE

Page n. 29 of 30

Material Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

K-FLEX K-400 ADHESIVE

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Exposure Scenarios

Substance HYDROCARBONS, C6-C7, ISOALCANS, CYCLICS, <5% n-HEXANE

Scenario Title HYDROCARBONS, C6-C7, ISOALKANS, CYCLICS, <5% n-HEXANE

Revision nr. 1

File EN_00038_1.pdf

Substance ACETONE

Scenario Title ACETONE

Revision nr. 1

File EN_00006_1.pdf

Substance ETHYL ACETATE

Scenario Title ACETATO DI ETHYLE

Revision nr. 1

File EN_00001_1.pdf

Substance HYDROCARBONS C6 ISOALCANS <5% n-HEXANE

Scenario Title ISOHEXANE

Revision nr. 1

File EN_00032_1.pdf